

eLakesideFoodservice.com/modifiable



## Ergo-One® SYSTEM UTILITY CARTS | STAINLESS STEEL

This beneficial cart was designed with the help of an orthopedic specialist to prevent body strain and unnecessary worker's comp expenses.

- Vertical handle with comfortable grip ensures wrists are in the correct position for pushing and steering
- Shelves are located within a "Safety Zone" that is the proper height for loading and unloading, bottom shelf is 20" (508) from the floor
- No-mark®, extra load, cushion tread wheels absorb impact, reducing vibration and strain
- 18-gauge stainless steel shelves reinforced for added strength
- All welded construction for a stronger structure and easier-to-clean surface
- Stainless steel is easy to clean and sanitize
- · Leg bumpers protect walls and furniture



## FACTORY INSTALLED OPTIONS (PAGE 55):

- Hi-Temp nylon casters, up to 400° F. (204° C.) 5" (127) 2 ea. fixed, 2 ea. swivel casters
- Lake-Glide casters and wheels
- Handle Set Both Ends
- Perimeter Channel Bumper
- 2 Brake Casters
- 4 5" Swivel Casters
- 2 5" Swivel, 2 5" Fixed Casters
- 2 5" Swivel, 2 -5" Fixed



Keep employees on the job. Injuries to the spine, wrist and major upper and lower body muscle groups can be caused by improper pushing, lifting and loading. The Ergo-One® system can reduce those injuries to minimize employee down time and workers' compensation claims.



	NSF					Overall Size				
Model	Model	# of Shelves	Shelf Size	Shelf Clearance	Top Shelf Height	w	L	Н	Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
7010	5910	2	18" x 27" (457 x 686)	18-1/2" (470)	40" (1016)	18-5/8" (473	35-3/8" 899	46-3/4" 1187)	53 (24)	18.8 (.73)
7015	5915	3	18" x 27" (457 x 686)	10" (254)	43" (1092)	18-5/8" (473	35-3/8" 899	46-3/4" 1187)	63 (28.6)	18.8 (.73)
7020	5920	2	21" x 33" (533 x 838)	18-1/2" (470)	40" (1016)	21-5/8" (549	41-3/8" 1051	46-3/4" 1187)	64 (29)	25.7 (1.0)
7025	5925	3	21" x 33" (533 x 838)	10" (254)	43" (1092)	21-5/8" (549	41-3/8" 1051	46-3/4" 1187)	78 (35.4)	27.4 (1.1)
7030	5930	2	21" x 49" (533 x 1245)	18-1/2" (470)	40" (1016)	21-5/8" (549	57-3/16" 1453	46-3/4" 1187)	127 (57.7)	80.1 (3.1)

Measurements in () denote metric millimeters, unless otherwise specified. Lake-Glide Casters: 5" (127) - 2 ea. swivel, 8" (203) - 2 ea. fixed, No-Mark, cushion tread.

