

REACH-IN FREEZER (0°F)

Model: 1FENPTHD

Natural Refrigerant R-290 Model

1-Section Extra-Wide Pass-Thru Freezer with Half Doors

- 1FENPTHD** - Stainless steel front, aluminum end panels and interior
- 1FENSAPTHD** - Stainless steel exterior, aluminum interior
- 1FENSSPTHD** - Stainless steel exterior and interior



Options and Accessories

(upcharge and lead times may apply)

| | |
|---|--|
| Additional epoxy coated steel shelves | Hinged glass doors (consult factory) |
| Chrome or stainless steel shelves | Rehinging of doors (consult factory) |
| Wine rack | Correctional Facility Options |
| Universal pan slides | <ul style="list-style-type: none"> • One way security screws |
| Adjustable legs | <ul style="list-style-type: none"> • Locking hasp (lock not included) |
| Custom laminates | <ul style="list-style-type: none"> • Stainless steel mesh cover |
| Special electrical requirements (consult factory) | <ul style="list-style-type: none"> • Coverless hinges |

Consult factory for other model configurations, options and accessories.

Continental
Refrigerator



Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Self contained, performance rated "plug" refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Refrigeration system is readily accessible on top of cabinet, separate from the "food zone"

Automatic, hot gas condensate evaporator

Expansion valve system

CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam action, lift off hinges

Self-closing doors

Magnetic snap in Santoprene™ door gaskets

Cylinder lock in each door

Heavy duty, epoxy coated steel shelves

Heavy duty pilaster strips

5" casters

MODEL FEATURES

LED interior lighting

Electronic control, automatic electric defrost

Top and side air distribution ducts

Cabinet upper side panels and refrigeration "plug" system can be removed and reinstalled at job site

¹ R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

Model Specifications

DIMENSIONAL DATA

| | |
|--|------------------|
| Net Capacity (cubic feet) | 22 (623 l) |
| Width, Overall (inches) | 28 1/2 (724 mm) |
| Depth, Overall (inches) (including handles) | 38 3/4 (984 mm) |
| Depth (inches) (less doors) | 32 (813 mm) |
| Depth (inches) (doors open 90°) | 84 (2134 mm) |
| Clear Door Width (inches) | 21 7/8 (556 mm) |
| Clear Half Door Height (inches) | 27 1/2 (699 mm) |
| Height, Overall (inches) (including 5" casters) | 82 1/4 (2096 mm) |
| Number of Doors | 4 |
| Number of Shelves | 3 |
| Shelf Area (square feet) | 20.4 (1.9 sq m) |
| Tray Slide Capacity (per half section) (2" centers) | 11 |

REFRIGERANT DATA

| | |
|-------------------------------|------|
| Condensing Unit Size (H.P.) | 1/2 |
| R-290 Refrigerant Charge (oz) | 4.3 |
| Capacity (BTU per hour)* | 1980 |

ELECTRICAL DATA



| | |
|--|---------------------|
| Voltage (International) | 115/60/1 (220/50/1) |
| Feed Wires (including ground) | 3 |
| Total Amps (International) | 6.3 (3.2) |
| Defrost Amps (International) | 4.4 (2.2) |
| 10 ft. Cord/Plug [attached] (International) | Yes (No) |

SHIPPING DATA

| | |
|------------------------------|------------------|
| Height - Crated (inches) | 85 1/2 (2172 mm) |
| Width - Crated (inches) | 31 5/8 (803 mm) |
| Depth - Crated (inches) | 42 (1067 mm) |
| Volume - Crated (cubic feet) | 65 (1841 cu l) |
| Weight Std - Crated (pounds) | 390 (177 kg) |
| Weight SS - Crated (pounds) | 465 (212 kg) |

* Rating @ -15°F evaporator, 90°F ambient
Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Model Plan Views



IMPORTANT NOTE: If the cabinet is located under a low ceiling, a minimum clearance of 12" is required on top and 3" on sides.

Continental
Refrigerator

Toll-Free: 800-523-7138
Phone: 215-244-1400
Fax: 215-244-9579

539 Dunksferry Road
Bensalem, PA 19020
www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



PROUDLY
DESIGNED & ASSEMBLED
IN THE U.S.A.

Intertek

© Copyright 2021. Continental Refrigerator.
A Division of National Refrigeration & Air Conditioning Products, Inc.



Equipped with one NEMA-5-15P Plug
(varies by country)

REVISED: 12/24/25