PRO CART ULTRA® - MODEL SPECIFICATIONS



	CODE	DESCRIPTION	UNIT Weight		
TALL PROFILE	Both Compartments Passive (Non-electric)				
	PCUPP	Both compartments non-electric / passive	235.2 lbs.		
	Both Compartments Hot				
	PCUHH	110V standard USA / CAN power cord 5-15P	267.5		
	PCUHH3	220V USA / CAN power cord 6-15P	268.4		
	Both Compartments Cold				
	PCUCC	110V standard USA / CAN power cord 5-15P	278.4		
	PCUCC3	220V USA / CAN power cord 6-15P	283.8		
	Combination Hot & Cold				
	PCUHC	Top compartment hot, bottom cold. 110V standard USA / CAN power cord 5-15P	271		
	PCUCH	Top compartment cold, bottom hot. 110V standard USA / CAN power cord 5-15P	271		
3 = 220V US/CAN/Mexico	PCUHC3	Top compartment hot, bottom cold. 220V standard USA / CAN power cord 6-15P	271.4		
	PCUCH3	Top compartment cold, bottom hot. 220V standard USA / CAN power cord 6-15P	271.4		
	Combination Passive & Hot or Cold				
	PCUPH	Top compartment passive, bottom hot. 110V standard USA / CAN power cord 5-15P	255.3		
	PCUPC	Top compartment passive, bottom cold. 110V standard USA / CAN power cord 5-15P	260.8		
	PCUPH3	Top compartment passive, bottom hot. 220V standard USA / CAN power cord 6-15P	255.8		
	PCUPC3	Top compartment passive, bottom cold. 220V standard USA / CAN power cord 6-15P	263.5		
LOW PROFILE	PCULP	Non-electric / passive	140		
	PCULH	Hot Cart, 110V standard USA / CAN power cord 5-15P	151		
	PCULC	Cold Cart, 110V standard USA / CAN power cord 5-15P	156		
	PCULH3	Hot Cart, 220V standard USA / CAN power cord 6-15P	151		
	PCULC3	Cold Cart, 220V standard USA / CAN power cord 6-15P	156		
Case Pack-1 C	nlor. Charcoal	Grav (615) Standard Railing Includes: 8 pairs of stainless steel Universal rails/compartment			

Case Pack: 1 Color: Charcoal Gray (615). Standard Railing Includes: 8 pairs of stainless steel Universal rails/compartment. Includes Standard Casters: 6" x 2" heavy duty swivel with brake in front, rigid in back.

Unit Dimensions

UNIT	EXTERIOR DIM. W x D x H	COMPARTMENT DIM. W x D x H
Tall Profile		
COLD	28" x 36½" x 66"	$21\frac{1}{8}$ " x $26\frac{1}{4}$ " x $25\frac{1}{2}$ "
HOT / PASSIVE	28" x 35¾" x 66"	21½" x 27" x 25½"
Low Profile		
COLD	28" x 36½" x 40"	$21\frac{1}{8}$ " x $26\frac{1}{4}$ " x $25\frac{1}{2}$ "
HOT / PASSIVE	28" x 35%" x 40"	21½" x 27" x 25½"

Optional Accessories

CODE	DESCRIPTION
PCMH / PCMH3	Hot module unit 110V / 220V
PCMC / PCMC3	Cold module unit 110V / 220V
SSR1	1 Pair of Rails
SSR8	8 Pairs of Rails

Case Pack: 1 Module Unit Color: Charcoal Gray (615).

Security Package (SP)

Specially designed for operations where safety and security are a top priority. To order add SP after the product code or visit cambro.com for a listing of codes.

- Tamper resistant fasteners secure side column panels to the cart.
- Cross locking rods behind column panels lock 5 rails in place.
- Each compartment holds ten 4" deep hotel pans.
- Passive and electrical modules and cord strap keepers are secured in place with tamper resistant fasteners.
- Non removable doors. Lockable hasp secures both doors at once. (Lock not included).
- Heavy duty casters mounted with tamper resistant fasteners.



All models are also available without rails and side column panels. Please visit cambro.com for details.



1.800.833.3003 CAMBRO USA-INSULATED TRANSPORT