




MOTION-CONNECT connection systems

Signal cables for SINAMICS S120

DRIVE-CLiQ signal cables without 24 V DC cores**Selection and ordering data****Pre-assembled DRIVE-CLiQ signal cables without 24 V DC cores**

Version	Length	D_{\max}	Connector/degree of protection, module-end	Connector/degree of protection, motor-end	DRIVE-CLiQ signal cable without 24 V DC cores
	m (ft)	mm (in)			Article No.
Fixed lengths 	0.11 (0.36)		RJ45/IP20	RJ45/IP20	6SL3060-4AB00-0AA0
	0.16 (0.52)				6SL3060-4AD00-0AA0
	0.21 (0.69)				6SL3060-4AF00-0AA0
	0.26 (0.85)				6SL3060-4AH00-0AA0
	0.31 (1.02)				6SL3060-4AK00-0AA0
	0.36 (1.18)				6SL3060-4AM00-0AA0
	0.41 (1.35)				6SL3060-4AP00-0AA0
	0.60 (1.97)				6SL3060-4AU00-0AA0
	0.95 (3.12)				6SL3060-4AA10-0AA0
	1.20 (3.94)				6SL3060-4AW00-0AA0
	1.45 (4.76)				6SL3060-4AF10-0AA0
	2.10 (6.89)				6SL3060-4AB20-0AA0
	2.80 (9.19)				6SL3060-4AJ20-0AA0
5.00 (16.4)		6SL3060-4AA50-0AA0			
To the decimeter	Max. 70 (230)	7.0 (0.28)	RJ45/IP20	RJ45/IP20	6FX2002-1DC00-....
					
To the decimeter	Max. 70 (230)	7.0 (0.28)	RJ45/IP67	RJ45/IP67	6FX2002-1DC20-....
					
Length code				