

TAPE-ROPE HYBRID

- Line voltage kits are economical - no drivers required
- High light output - up to 80 lumens/ft in a compact size
- Low profile flexible housing measures only 3/8" wide and 1/4" high
- Easy to install - kits interconnect and plug into standard 120V AC receptacles
- Suitable for indoor and outdoor installations
- While Supplies Last

TAPE ROPE HYBRID



PART NUMBER	LENGTH	WATTS	COLOR
120V - 60 LEDs per meter - 6 per case			
120-TL60-3.3-___*	3.3 ft	4.8W	(BL) = BLUE
120-TL60-6.6-___*	6.6 ft	9.6W	(GR) = GREEN
120-TL60-13.2-___*	13.2 ft	19.2W	(RE) = RED
120-TL60-19.7-___*	19.7 ft	28.8W	(WH) = BRIGHT WHITE
120-TL60-32.8-___*	32.8 ft	48W	(WW) = WARM WHITE
120-TL60-45.9-___*	45.9 ft	67.2W	

*Specify Color



ACCESSORIES

PART NUMBER	ITEM DESCRIPTION
120-TL-TRACK4	4 ft Clear plastic track
120-TL-JUMP-3	3 ft linking extension (jumper)
120-TL-JUMP-6	6 ft linking extension (jumper)
120-TL-JUMP-15	15 ft linking extension (jumper)



Clear Plastic Track
(120-TL-TRACK4)



3 ft Jumper
(120-TL-JUMP-3)



6 ft Jumper
(120-TL-JUMP-6)



15 ft Jumper
(120-TL-JUMP-15)

TECHNICAL SPECIFICATIONS

Voltage	120V, 60 Hz AC operation (1.6A inverter on cord converts AC power to DC for LEDs)
Construction	LEDs spaced every .65" inside durable white PVC housing with clear PVC jacket
Wattage	Listed above, except 3.3 ft RE = 2.4W, 6.6 ft RE =4.8W, 13.2 ft RE =9.6W, 19.7 ft RE =14.4W, 32.8 ft RE =24W, 45.9 ft RE =33.6W
Maximum run	Interconnect WH and WW up to 106 ft; BL and GR up to 106 ft; Red up to 211 ft
Power cord	Bulk reels have 24" lead wire; kits have 6 ft fused power cord molded to 24" lead
Case Qty	6 per case