


SPHERICAL PLAIN BEARINGS – METRIC

GE...TA 2RS SERIES



Specifications

- Sliding Surface: PTFE Lined Steel Outer on Chrome Plated Ball
- Maintenance Free - Low Friction

Part #	Dimensions (inches)								Load Ratings kN		Weight LBS
	d	D	B	C	d _k	r _s min	r _{is} min	α ≈	Dynamic	Static	
GE 100TA 2RS	100	150	70	55	130	1	1	7	1070	2140	9.81
GE 110TA 2RS	110	160	70	55	140	1	1	6	1150	2300	10.63
GE 120TA 2RS	120	180	85	70	160	1	1	6	1680	3360	17.75
GE 140TA 2RS	140	210	90	70	180	1	1	7	1890	3780	24.29
GE 160TA 2RS	160	230	105	80	200	1	1	8	2400	4800	30.89
GE 180TA 2RS	180	260	105	80	225	1.1	1.1	6	2700	5400	41.12
GE 200TA 2RS	200	290	130	100	250	1.1	1.1	7	3750	7500	61.8
GE 220TA 2RS	220	320	135	100	275	1.1	1.1	8	4120	8240	78.29
GE 240TA 2RS	240	340	140	100	300	1.1	1.1	8	4500	9000	87.99
GE 260TA 2RS	260	370	150	110	325	1.1	1.1	7	5360	10720	113.63
GE 280TA 2RS	280	400	155	120	350	1.1	1.1	6	6300	12600	143.43
GE 300TA 2RS	300	430	165	120	375	1.1	1.1	7	6750	13500	172.11

Common Interchanges (100mm Bore): SAR1-100SS RBC, GE100 UK-2RS INA, GE100EC-2RS IKO, GE100C-2RS CONS

