



For more Information
please call

1-800-Belden1



General Description:

Security & Alarm Cable, Riser-CMR, 2-18 AWG stranded bare copper pairs with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 2 | 18 | 7x26 | BC - Bare Copper |

Total Number of Conductors: 4

Insulation

Insulation Material:

| Insulation Material | Wall Thickness (mm) |
|---------------------|---------------------|
| PP - Polypropylene | 0.178 |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Outer Shield Material |
|-------------------------|------------------------------|
| Beldfoil® | Aluminum Foil-Polyester Tape |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | Solid | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material | Nom. Wall Thickness (mm) |
|--------------------------|--------------------------|
| PVC - Polyvinyl Chloride | 0.432 |

Overall Cable

Overall Nominal Diameter: 6.350 mm

Pair

Pair Color Code Chart:

| Number | Color |
|--------|---------------|
| 1 | Black & Red |
| 2 | Black & White |

Mechanical Characteristics (Overall)

| | |
|-----------------------------------|----------------|
| Operating Temperature Range: | -20°C To +70°C |
| Bulk Cable Weight: | 49.111 Kg/Km |
| Max. Recommended Pulling Tension: | 460.834 N |
| Min. Bend Radius/Minor Axis: | 63.500 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|------------|
| NEC/(UL) Specification: | CMR |
| CEC/C(UL) Specification: | CMG |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |

METRIC MEASUREMENT VERSION

5341FE Multi-Conductor - Commercial Applications

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

Flame Test

UL Flame Test: UL1666 Vertical Shaft

CSA Flame Test: FT4

Plenum/Non-Plenum

Plenum (Y/N): No

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

95.149

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

171.432

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

21.4905

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

42.981

Max. Operating Voltage - UL:

Voltage

300 V RMS

Max. Recommended Current:

| Description | Current |
|----------------------|-------------------------------------|
| 10C Temperature Rise | 4 Amps per conductor @ 25°C ambient |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|-----------------|----------|-------------|-------|-------|----------------------|
| 5341FE 008U1000 | 1,000 FT | 35.000 LB | GRAY | | 2 PR #18 PP FS FRPVC |
| 5341FE 0081000 | 1,000 FT | 36.000 LB | GRAY | C | 2 PR #18 PP FS FRPVC |
| 5341FE 0081200 | 1,200 FT | 43.200 LB | GRAY | | 2 PR #18 PP FS FRPVC |
| 5341FE 0081500 | 1,500 FT | 54.000 LB | GRAY | | 2 PR #18 PP FS FRPVC |
| 5341FE 008500 | 500 FT | 21.000 LB | GRAY | C | 2 PR #18 PP FS FRPVC |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 08-20-2013

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).