

CFP-LSCS
EDGE-LIT FLAT PANEL

DATE: _____ LOCATION: _____
 TYPE: _____ PROJECT: _____
 CATALOG #: _____

tradeSELECT®

FEATURES

- Switchable Lumen technology:
5500/4100/3400 lumens (1x4, 2x4)
4000/3300/2800 lumens (2x2)
- Switchable CCT technology: 3500/4000/5000K
- 80 CRI
- 0–10V dimming to 10%
- Recessed, surface, or cable mount
- Universal voltage (120–277V)
- IC rated
- Suitable for ISO Class 5–9 positive pressure cleanrooms



SPECIFICATIONS

CONSTRUCTION

- Extruded aluminum frame has a matte white finish and smooth frame-to-lens transition

OPTICS

- Acrylic blend light guide with frosted/textured outer lens provides edge to edge illumination without pixelation or bright spots

INSTALLATION

- Integral T-bar clips for secure mounting to grid ceiling
- For surface/cable mount applications use surface/cable mount kit accessories
- For plaster or sheet rock installations, use flange kit

ELECTRICAL

- 54,000 hour LEDs at L70 for reduced maintenance
- Switchable Lumen technology allows for easy field-adjustable lighting output with three level switch located on back of panel
- Switchable Lumen fixtures ship at the highest lumen output setting
- Operates at 120-277V input
- 0–10V dimmable driver, down to 10%

CERTIFICATIONS

- All luminaires are built to UL 1598 standards and bear appropriate cULus labels
- Certified to UL 924 standards with battery pack

CERTIFICATIONS (CONTINUED)

- Damp location label standard
- Tested in accordance with ISO 14644-1; suitable for ISO Class 5–9 positive pressure cleanrooms
- Adheres to LM79, LM80, and TM21 industry standards for photometrics and lifetime calculations
- DLC® (DesignLights Consortium Qualified, with some Premium Qualified configurations. Please refer to the DLC website for specific product qualifications at www.designlights.org)

WARRANTY

- 5 year warranty
- See [HLI Standard Warranty](#) for additional information

ORDERING GUIDE

| Catalog No. | UPC | Description | Setting | Lumens | | | Watts | LPW | | |
|--|--------------|--|---------|--------|-------|-------|-------|-------|-------|-------|
| | | | | 3500K | 4000K | 5000K | | 3500K | 4000K | 5000K |
| <input type="checkbox"/> CFP14-LSCS | 840141401867 | 1x4 Edge-Lit Panel, 5500/4100/3400 Switchable Lumens, 3500/4000/5000K Switchable CCT | LOW | 3516 | 3540 | 3478 | 29 | 119 | 120 | 118 |
| | | | MED | 4204 | 4257 | 4163 | 36 | 117 | 119 | 116 |
| | | | HIGH | 5617 | 5706 | 5522 | 50 | 112 | 113 | 110 |
| <input type="checkbox"/> CFP22-LSCS | 840141401874 | 2x2 Edge-Lit Panel, 4000/3300/2800 Switchable Lumens, 3500/4000/5000K Switchable CCT | LOW | 3174 | 3225 | 3137 | 24 | 131 | 133 | 129 |
| | | | MED | 3603 | 3679 | 3562 | 28 | 128 | 131 | 127 |
| | | | HIGH | 4381 | 4477 | 4291 | 35 | 124 | 127 | 122 |
| <input type="checkbox"/> CFP22-33CS-HE | 840141421933 | 2x2 Edge-Lit Panel, 3300 Lumens, 3500/4000/5000K Switchable CCT | — | 3620 | 3699 | 3617 | 29 | 125 | 128 | 125 |
| <input type="checkbox"/> CFP24-LSCS | 840141401881 | 2x4 Edge-Lit Panel, 5500/4100/3400 Switchable Lumens, 3500/4000/5000K Switchable CCT | LOW | 3394 | 3387 | 3279 | 25 | 134 | 133 | 129 |
| | | | MED | 4291 | 4318 | 4231 | 33 | 129 | 130 | 127 |
| | | | HIGH | 6011 | 6065 | 5856 | 49 | 122 | 123 | 119 |
| <input type="checkbox"/> CFP24-41CS-HE | 840141421971 | 2x4 Edge-Lit Panel, 4100 Lumens, 3500/4000/5000K Switchable CCT | — | 4428 | 4507 | 4420 | 35 | 127 | 129 | 126 |
| <input type="checkbox"/> CFP24-75CS | 840141421995 | 2x4 Edge-Lit Panel, 7500 Lumens, 3500/4000/5000K Switchable CCT | — | 7509 | 7742 | 7388 | 62 | 121 | 125 | 119 |

| KEY DATA | |
|-----------------------|------------|
| Lumen Range | 3137–7742 |
| Wattage Range | 24–62 |
| Efficacy Range (LPW) | 110–134 |
| Reported Life (Hours) | L70/54,000 |

SEE FOLLOWING PAGE FOR CFP ACCESSORIES

ORDERING GUIDE

| Accessories (Order Separately) | |
|--------------------------------|---|
| PLD10M | Dual-Lite® Emergency LED Battery Pack, field installed ¹ |
| PLRTS | Remote Test Switch/Charge Indicator Module (fits single-gang box) |
| FK14 | 1x4 Single Flange Kit |
| FK22 | 2x2 Single Flange Kit |
| FK24 | 2x4 Single Flange Kit |
| SRPSMK-14 | 1x4 CFP Surface Mount Kit |
| SRPSMK-22 | 2x2 CFP Surface Mount Kit |
| SRPSMK-24 | 2x4 CFP Surface Mount Kit |
| CFPCM36Y SC5F-KIT | 36" Cable Mount Kit for 1' or 2' wide Cable Mount fixtures, 5-wire |


Notes:

1 Fixtures with Emergency Battery Pack require a remote-mounted test switch, we suggest the Dual-Lite PLRTS.


CFP-LSCS
EDGE-LIT FLAT PANEL

DIMENSIONS


1'x4' Recessed Mount




1'x4' Surface Mount




2'x2' Recessed Mount




2'x2' Surface Mount



2'x4' Recessed Mount



2'x4' Surface Mount



PHOTOMETRY

CFP14-LSCS


LUMINAIRE DATA

| | |
|-------------------|--|
| Test No. | 20.01296 |
| Description | 1x4 LED Flat-Panel; Lumen Switchable, Color Switchable |
| Delivered Lumens | 4295 |
| Watts | 35.9 |
| Efficacy | 120 |
| Mounting | Recessed |
| Spacing Criterion | 0° = 1.27 90° = 1.25 |

ZONAL LUMEN SUMMARY

| Zone | Lumens | % Luminaire |
|-------|--------|-------------|
| 0-30 | 1153 | 26.8 |
| 0-40 | 1891 | 44.0 |
| 0-60 | 3358 | 78.2 |
| 0-90 | 4295 | 100.0 |
| 0-180 | 4295 | 100.0 |

POLAR GRAPH



CFP22-LSCS


LUMINAIRE DATA

| | |
|-------------------|--|
| Test No. | 20.01303 |
| Description | 2x2 LED Flat-Panel; Lumen Switchable, Color Switchable |
| Delivered Lumens | 2851 |
| Watts | 25.1 |
| Efficacy | 114 |
| Mounting | Recessed |
| Spacing Criterion | 0° = 1.26 90° = 1.26 |

ZONAL LUMEN SUMMARY

| Zone | Lumens | % Luminaire |
|-------|--------|-------------|
| 0-30 | 765 | 26.8 |
| 0-40 | 1255 | 44.0 |
| 0-60 | 2230 | 78.2 |
| 0-90 | 2851 | 100.0 |
| 0-180 | 2851 | 100.0 |

POLAR GRAPH



CFP24-75CS

LUMINAIRE DATA

| | |
|-------------------|--------------------------------------|
| Test No. | 20.01300 |
| Description | 2x4 LED Flat-Panel; Color Switchable |
| Delivered Lumens | 7747 |
| Watts | 59.0 |
| Efficacy | 131 |
| Mounting | Recessed |
| Spacing Criterion | 0° = 1.27 90° = 1.26 |

ZONAL LUMEN SUMMARY

| Zone | Lumens | % Luminaire |
|-------|--------|-------------|
| 0-30 | 2072 | 26.7 |
| 0-40 | 3402 | 43.9 |
| 0-60 | 6050 | 78.1 |
| 0-90 | 7747 | 100.0 |
| 0-180 | 7747 | 100.0 |

POLAR GRAPH

