



Item # 20016808, VERSIFLO 125 Water Discharge Hose 2 in x 100 ft, 125 psi, Black

APPLICATION: For medium-duty water discharge service where the hose does not encounter severe handling.

CONSTRUCTION TUBE: Black EPDM(compound)® synthetic rubber

COVER: Black EPDM(compound) (wrapped finish)

REINFORCEMENT: Spiral-plied synthetic fabric

TEMPERATURE: -25 °F to 180 °F (-32 °C to 82 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech Versiflo® 125 Water Discharge.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Water Transfer
Style	Water Suction and Discharge Hose
Construction Tube	Black Versigard® synthetic rubber
Cover	Black Versigard (wrapped finish)
Reinforcement	Spiral-plied synthetic fabric
Color	Black
Min. Temperature	-25 °F

	-32 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	125.0 psi 0.86 MPa
Brand	PLICORD® VERSIFLO® 125
Order Code	542-527

Specifications

I.D.	2 in 50.80 mm
Nom. O.D.	2.240 in 56.90 mm
Length	100.000 ft
Weight	0.400 lb/ft 0.60 kg/m

MideastUS@contitech.us
1-800-235-4632
Contitech.us

ContiTech