



## Item # 20019292, WHITE FLEXWING Food Hose 2 in x 100 ft, 150 psi, White

**APPLICATION:** A highly flexible hose for gravity flow, pressure, or suction service transferring oily and nonoily edibles from tank truck and in-plant service.

**CONSTRUCTION TUBE:** White Chemivic™ synthetic rubber (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03)

**COVER:** White Chemivic synthetic rubber (wrapped impression)

**REINFORCEMENT:** Spiral-plyed synthetic fabric with galvanized wire helix

**TEMPERATURE:** -25 °F to 230 °F (-32 °C to 110 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendations and coupling procedure.

**BRANDING (SPIRAL):** Example: Continental Contitech White Flexwing® 150 psi WP; FDA, 3-A, and USDA.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

<b>Style</b>	Food Hose
<b>Construction Tube</b>	White Chemivic™ synthetic rubber (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03)
<b>Cover</b>	White Chemivic synthetic rubber (wrapped impression)
<b>Reinforcement</b>	Spiral-plyed synthetic fabric with galvanized wire helix
<b>Color</b>	White
<b>Min. Temperature</b>	-25 °F

	-32 °C
<b>Max. Temperature</b>	230 °F 110 °C
<b>Max. Working Pressure</b>	150.0 psi 1.03 MPa
<b>Packaging</b>	Coil
<b>Order Code</b>	549-151
<b>Edited By: Initials and Date</b>	SAS 12/13/12
<b>Brand</b>	WHITE FLEXWING®

### Specifications

<b>I.D.</b>	2 in 50.80 mm
<b>Nom. O.D.</b>	2.530 in 64.30 mm
<b>Length</b>	100.000 ft
<b>Bend Radius</b>	5.000 in 114.00 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	1.230 lb/ft 1.83 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**