

Eaton C25DND330H

Catalog Number: C25DND330H

Eaton definite purpose contactor, Quick, 30A, 277 Vac, 60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 30A, Contactor, Three-pole, 40A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25DND330H
UPC	Product Length/Depth
782116308897	3.35 in
Product Height	Product Width
2.5 in	2.4 in
Product Weight	Warranty
1.05 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Recognized CSA Certified

Product specifications

Frame size

15-50 A, two-pole and three-pole

Type

Non-reversing

Inductive full load

30 A

Model

Contactor

Connection

Quick

Enclosure

Open with metal mounting plate

Terminals

Screw/pressure plate and quick connect terminals (side-by-side)

Amperage Rating

30A

Resistive load

40 A

Number Of Poles

Three-pole

Coil

277 Vac, 60 Hz

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[C25DND3 AutoCAD 2D Footprint \(mm\)](#)

[C25DND3 AutoCAD 2D Footprint](#)

[C25DND3 3D Inventor](#)

[C25DND3 2D Drawing Xchange](#)

[C25DND3 3D Model Xchange](#)

[C25DND3 2D PDF](#)

Specifications and datasheets

[Eaton Specification Sheet - C25DND330H](#)