

Catalog Number: RB 6214 SL
Product ID: 7TAA260520R0038
UPC Number: 78378674571
Status: A

EPDM Rubber Insulated Mechanical Streetlight Aluminum Connector, Main Body 5 inch wide x 1-5/8 inch tall x 1-10/32 inch deep - with mounting tabs on each side. Six ports on top for #12 to #2 Streetlight Wire. Twelve 3/8 long ports on side for Set Screws and Caps. Six ports on bottom for 1/0 Max Feeder Wires. Includes Twelve Orange Caps, Twelve 5/16-24 x 15/32 inch Tin Plated Screws (use 1/8 inch Hex Key Type Wrench).

- Rubber Insulation Ensures an Insulated Connection
- Models with Streetlight Connectors Fit a Range of Mains and Taps.

North American Specifications (UNSPSC)

UNSPSC	39121408 Mechanical connectors
IGCC	4541 Mechanical connectors
Brand Name	Homac
Type	Streetlight Connector
Special Features	Insulated, Hardware and Caps
Connection	Mechanical
Material	Aluminum
Insulation	EPDM Rubber
Conductor Range (Main/Primary)	1/0 AWG

Packaging

Outer Quantity	25
Outer Dimensions (inches)	11.75x6x8.5
Weight Uom	0.41 lbs. Each

Documents / Support Tools

Catalog	Available on Website
---------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com