

Hub City™ Worm Gear Drives

Single Reduction

PowerCubeX® Worm Speed Reducer Catalog Ratings

Series 180

SERIES	INPUT RPM	RATIO	OUTPUT RPM	CONVENTIONAL OIL					PAO SYNTHETIC OIL			PAG SYNTHETIC OIL		
				MECH. INPUT HP	EFF. %	MECH. OUTPUT TORQUE	THERMAL INPUT HP	THERMAL OUTPUT TORQUE	INPUT HP	EFF. %	OUTPUT TORQUE	INPUT HP	EFF. %	OUTPUT TORQUE
180	2500	5	500	3.00	86.8	328	2.11	231	3.00	92.0	348	3.00	94.8	358
		7.5	333	2.40	85.6	389	1.61	261	2.40	90.8	413	2.40	93.6	425
		10	250	1.96	84.7	418	1.42	304	1.96	89.8	443	1.96	92.6	457
		15	167	1.48	81.5	455	1.00	307	1.48	86.4	483	1.48	89.1	498
		20	125	1.16	79.8	465	1.04	416	1.16	84.6	493	1.16	87.2	509
		25	100	0.95	78.0	466	0.80	397	0.95	82.7	494	0.95	85.2	509
		30	83.3	0.84	74.0	471	0.68	383	0.84	78.4	499	0.84	80.8	515
		40	62.5	0.65	71.1	465	THERMAL EQUALS MECHANICAL		0.65	75.4	493	0.65	77.8	509
		50	50.0	0.52	68.2	449			0.52	72.4	476	0.52	74.6	491
		60	41.7	0.43	65.0	427			0.43	68.9	452	0.43	71.0	466
		80	31.3	0.28	60.8	348			0.28	64.4	369	0.28	66.4	380
		100	25.0	0.191	56.7	272			0.191	60.1	289	0.191	61.9	298
	1750	5	350	2.57	85.9	397	2.04	315	2.57	91.1	421	2.57	93.9	434
		7.5	233	2.05	84.7	468	1.53	349	2.05	89.7	496	2.05	92.5	511
		10	175	1.63	83.6	491	1.34	404	1.63	88.6	520	1.63	91.4	536
		15	117	1.25	80.0	541	1.00	446	1.25	84.8	573	1.25	87.4	591
		20	87.5	1.00	78.0	541	0.90	510	1.00	82.7	574	1.00	85.3	591
		25	70.0	0.78	76.0	536	0.75	520	0.78	80.6	569	0.78	83.1	586
		30	58.3	0.75	71.5	557	0.64	495	0.75	75.8	590	0.75	78.1	609
		40	43.8	0.55	68.5	540	THERMAL EQUALS MECHANICAL		0.55	72.6	572	0.55	74.8	590
		50	35.0	0.44	65.4	516			0.44	69.3	547	0.44	71.4	564
		60	29.2	0.37	61.9	490			0.37	65.6	520	0.37	67.6	536
		80	21.9	0.25	57.5	395			0.25	61.0	419	0.25	62.9	432
		100	17.5	0.160	53.3	308			0.160	56.5	326	0.160	58.2	336
	1170	5	234	2.02	84.9	461	1.84	419	2.02	90.0	489	2.02	92.8	504
		7.5	156	1.60	83.5	540	1.40	472	1.60	88.5	572	1.60	91.2	590
		10	117	1.25	82.3	555	THERMAL EQUALS MECHANICAL		1.25	87.2	589	1.25	89.9	607
		15	78.0	1.00	78.1	617			1.00	82.8	654	1.00	85.3	675
		20	58.5	0.75	76.0	608			0.75	80.6	644	0.75	83.1	664
		25	46.8	0.60	73.8	598			0.60	78.2	634	0.60	80.6	654
		30	39.0	0.57	68.7	634			0.57	72.8	672	0.57	75.0	693
		40	29.3	0.43	65.5	606			0.43	69.4	642	0.43	71.5	662
		50	23.4	0.34	62.2	575			0.34	65.9	610	0.34	68.0	629
		60	19.5	0.29	58.5	546			0.29	62.0	579	0.29	63.9	597
		80	14.6	0.187	54.0	436			0.187	57.3	462	0.187	59.0	476
		100	11.7	0.126	49.7	338			0.126	52.7	358	0.126	54.3	369
	100	5	20.0	0.244	79.1	607	THERMAL EQUALS MECHANICAL		0.244	83.8	644	0.244	86.4	664
		7.5	13.3	0.194	76.6	702			0.194	81.2	744	0.194	83.8	767
		10	10.0	0.147	75.2	697			0.147	79.7	739	0.147	82.2	762
		15	6.7	0.122	68.3	788			0.122	72.4	836	0.122	74.7	861
		20	5.0	0.091	65.8	754			0.091	69.8	799	0.091	71.9	824
		25	4.0	0.074	63.0	731			0.074	66.8	775	0.074	68.8	799
		30	3.3	0.077	55.3	806			0.077	58.7	854	0.077	60.5	881
		40	2.5	0.057	52.0	748			0.057	55.2	793	0.057	56.9	818
		50	2.0	0.046	48.5	702			0.046	51.4	744	0.046	53.0	767
		60	1.7	0.040	44.4	666			0.040	47.1	706	0.040	48.5	728
		80	1.3	0.026	40.2	521			0.026	42.7	553	0.026	44.0	570
		100	1.0	0.018	36.1	402			0.018	38.3	426	0.018	39.5	439

ADDITIONAL RATINGS FOR OTHER INPUT SPEEDS ARE AVAILABLE AT WWW.REGALBELOIT.COM

OVERHUNG LOAD AND THRUST LOAD INFORMATION

OVERHUNG LOAD - LOW SPEED SHAFT.

MODELS 181 AND 184 550 LBS. AT CENTER POINT OF SHAFT EXTENSION. MODELS 182 AND 185 NOT APPLICABLE.

THRUST± UP OR DOWN 600 LBS.

±OHL AND THRUST VALUES SHOWN ARE INDEPENDENT FUNCTIONS AND CANNOT BE APPLIED SIMULTANEOUSLY.


REFER APPLICATIONS WITH COMBINED OHL AND THRUST TO REGAL CUSTOMER SERVICE DEPARTMENT.

OUTPUT TORQUE VALUES SHOWN ARE INCH-POUNDS (IN-LB).

Hub City™ Worm Gear Drives

Single Reduction Models

134, 154, 184, 214, 244, 264, 304, 324, 384, 424, 454, 524, GW604




SPECIAL, METRIC AND SAE HYDRAULIC INPUT FLANGES AVAILABLE.
CONSULT FACTORY FOR COMPLETE SPECIFICATIONS.

ALL GW MODELS ARE FAN COOLED
REFER TO FAN DETAILS ON NEXT PAGE.

FOR LUBRICATION AND INSTALLATION INSTRUCTIONS -
REFER TO SECTION M

DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.
DOWNLOAD AVAILABLE CAD MODELS AT:
WWW.HUBCITYINC.COM

Standard Styles Available



CONSULT FACTORY FOR VERTICAL SHAFT LUBRICATION RECOMMENDATIONS.
INPUT SHAFT CAN BE ROTATED IN EITHER DIRECTION.

Hub City™ Worm Gear Drives

Single Reduction Models


134, 154, 184, 214, 244, 264, 304, 324, 384, 424, 454, 524, GW604

MODEL	C.D.	A	B	D	E	Q1	Q2
134	1.334	2.61	1.186	1.562	4.082	4.12	3.12
154	1.541	3.14	1.928	1.906	5.375	4.88	3.44
184	1.751	3.23	1.374	1.875	5.000	5.16	3.44
214	2.064	3.61	1.500	2.437	6.000	5.88	4.12
244	2.376	3.77	2.061	2.500	6.937	6.12	4.06
264	2.626	4.33	1.874	2.938	7.438	7.20	4.50
304	3.001	4.84	2.624	3.250	8.875	8.12	5.25
324	3.251	5.28	2.124	3.250	8.625	8.62	5.20
384	3.751	4.90	2.374	3.937	10.062	9.60	5.62
424	4.251	6.10	2.686	4.438	11.375	10.25	6.13
454	4.501	5.23	2.499	4.625	11.625	9.25	4.63
524	5.168	5.98	2.624	5.375	13.167	10.75	5.06
GW604	6.000	N/A	4.000	6.500	16.500	14.25	8.13

MODEL	S	T	U	V1	V2	W	X	Y
134	6.50	3.25	.625/.624	1.69	1.53	1.60	3/16 X 3/32	1.38
154	8.62	4.31	.750/.7485	2.11	1.90	2.08	3/16 X 3/32	1.51
184	7.00	3.50	.750/.749	1.78	1.57	1.54	3/16 X 3/32	1.41
214	8.50	4.25	.875/.874	2.19	1.98	1.95	3/16 X 3/32	1.83
244	10.28	5.14	1.125/1.1235	2.66	2.44	2.62	1/4 x 1/8	1.76
264	9.00	4.50	1.250/1.249	2.25	2.04	N/A	1/4 x 1/8	1.85
304	13.50	6.75	1.250/1.2485	3.60	3.36	3.57	1/4 X 1/8	2.26
324	10.88	5.44	1.375/1.374	2.84	2.62	2.75	5/16 X 5/32	2.31
384	13.38	6.69	1.500/1.499	3.88	N/A	N/A	3/8 X 3/16	3.16
424	16.24	8.12	1.875/1.8735	4.50	4.21	4.47	1/2 X 1/4	3.06
454 **	14.50	7.25	1.625/1.624	4.18	N/A	3.90	3/8 X 3/16	3.28
524 ***	15.62	7.81	1.750/1.749	4.47	N/A	4.17	3/8 X 3/16	3.50
GW604	20.00	10.00	2.500	4.65	4.65	N/A	5/8 X 5/16 P&W	4.00

** ALSO AVAILABLE WITH 1.750/1.749 (U) DIAMETER OUTPUT SHAFT. CONSULT FACTORY.
 *** ALSO AVAILABLE WITH 2.000/1.999 (U) DIAMETER OUTPUT SHAFT. CONSULT FACTORY.

Fan Detail for Model GW604



MODEL	A	FA	FB	FC
GW604	N/A	11.13	9.50	4.00

ALL GW MODELS ARE FAN COOLED.

MODEL	G	I	I2	N	N2
134	48CZ	3.46	N/A	4.36	3.87
	56C			6.63	6.50
154	48CZ	3.99	N/A	4.36	3.87
	56C			6.63	6.50
	143TC				
184	48CZ	4.09	N/A	4.36	3.87
	56C			6.63	6.50
	143TC				
214	48CZ	4.46	N/A	4.36	3.87
	56C			6.63	6.50
	143TC				
244	56C	4.63	N/A	6.50	6.50
	143TC				
	182TC			5.06	9.00
264	56C	5.19	N/A	6.50	6.50
	143TC				
	182TC			5.81	9.00
304	56C	5.95	N/A	6.50	6.50
	143TC				
	182TC			6.15	9.00
	213TC			6.71	
324	56C	6.14	N/A	6.50	6.50
	143TC				
	182TC			6.34	9.00
	213TC			6.90	
384	56C	6.50	N/A	6.50	6.50
	143TC				
	182TC			6.88	9.00
424	56C	6.45	N/A	6.50	6.50
	143TC				
	182TC				
	213TC			7.21	9.00
	254TC			7.77	
454	56C	6.75	N/A	6.50	6.50
	143TC				
	182TC			6.75	9.00
	213TC				
524 *	182TC	N/A	7.50	9.00	9.00
	213TC				
GW604	56C	10.45	N/A	6.50	6.50
	143TC				
	182TC				
	213TC			9.33	9.00
	254TC			9.94	

* 56C & 143TC FLANGES AVAILABLE AS MODIFIED STANDARDS

MODEL	AA	BB	CC	DD	EE	FF	GG	HH	JJ	KK	LL	MM	NN	OO	Wt. Lbs.
134	2.250	1.125	1.625	0.813	1/4 UNC	0.50	0.50	3.250	1.625	2.000	1.000	5/16 UNC	0.50	0.50	12
154	4.188	2.094	2.750	1.375	5/16 UNC	0.63	0.63	N/A	N/A	N/A	N/A	N/A	N/A	N/A	16
184	3.125	1.563	1.625	0.813	1/4 UNC	0.50	0.50	4.188	2.094	2.750	1.375	5/16 UNC	0.63	0.63	16
214	4.000	2.000	2.000	1.000	3/8 UNC	0.50	0.70	5.000	2.500	2.875	1.438	3/8 UNC	0.70	0.70	25
244	5.000	2.500	2.875	1.438	3/8 UNC	0.69	0.69	N/A	N/A	N/A	N/A	N/A	N/A	N/A	38
264	4.875	2.438	2.688	1.344	3/8 UNC	0.70	0.70	6.375	3.188	3.375	1.688	3/8 UNC	0.70	0.70	38
304	7.000	3.500	4.000	2.000	7/16 UNC	0.88	0.88	N/A	N/A	N/A	N/A	N/A	N/A	N/A	61
324	6.250	3.125	2.750	1.375	1/2 UNC	0.75	0.75	7.500	3.750	4.000	2.000	7/16 UNC	0.88	0.88	67
384	6.875	3.438	3.000	1.500	1/2 UNC	0.94	1.00	8.500	4.250	4.750	2.375	1/2 UNC	1.00	1.00	90
424	8.500	4.250	5.000	2.500	5/8 UNC	1.00	1.00	N/A	N/A	N/A	N/A	N/A	N/A	N/A	112
454	8.125	4.063	3.250	1.625	5/8 UNC	0.88	1.13	N/A	N/A	N/A	N/A	N/A	N/A	N/A	112
524	9.500	4.750	3.750	1.875	5/8 UNC	1.00	1.25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	138
GW604	12.750	6.375	6.380	3.190	5/8 UNC	1.00	1.00	N/A	N/A	N/A	N/A	N/A	N/A	N/A	324