



BURNDY Catalog Number
UPC Number
Description
Status

YGIBS286752N
 7818100393422
 .675 STD FLNG, 2-4/0
 Active

Web Use
 BURNDY Product Line

Dimensional	
Length (in)	3.00
B Length (in)	3.00
E - in	1.75
B Length (Fraction)	3
General	
Product Description	I-Beam Connector For Copper Cable, 2 - 4/0 AWG, 3 in L, Groundlink, I-Beam Flange Thickness: 0.613" - 0.675"
Conductor(s)	
Copper Stranded (Range)	2 AWG-4/0 AWG
Physical	
Type of Plating	Unplated
Connector Type	Tap
I Beam Style	Standard Beam (Flange Angled)
I Beam Thickness	0.563, 0.600, 0.625, 0.575
I Beam Thickness (Range)	0.613" - 0.675"
Plated (Yes or No)	N
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175