



BURNDY Catalog Number Q3A344N
 UPC Number 781810323649
 Description 400-500 CU 3 COND 4 HO
 Status Active

Web Use
 BURNDY Product Line

| Dimensional | |
|-------------------------------|---|
| Height (Fraction) (in) | 1-15/16 |
| Length (in) | 4.69 |
| Thickness (in) | 3/8 |
| Height (in) | 2 |
| D or Diameter (Fraction) (in) | 3-1/8 |
| Hole Size (Fraction) | 9/16 |
| Stud Size (in) | 1/2 |
| Thickness | 0.38 |
| D - in | 3.13 |
| Pad Width (in) | 3 |
| N (Fraction) | 5/8 |
| E - in | 1.75 |
| N (in) | 0.63 |
| Hole Size (in) | 0.56 |
| Length (Fraction) | 4-3/4 |
| General | |
| Number of Holes | 4 |
| Product Description | Copper Terminal, 4 Hole, 400-500 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, 3 Screws |
| Conductor(s) | |
| Copper Solid Size (Range) | N/A |
| Navy Cable Size (Range) | N/A |
| Copper Stranded (Range) | 400 kcmil-500 kcmil |
| Physical | |
| Installation Torque | 375 |
| Type of Plating | Unplated |
| Connector Type | Terminal |
| Plated (Yes or No) | N |
| Product Material | Copper |
| Approvals / Certifications | |
| UL Listed | Y |
| CSA Certified | N |
| ROHS Compatible | Exempt |
| UL Recognized | N |
| CULUS | N |
| Industry Standards | UL468A-468B |
| Documentation | |

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM

Monday - Friday

Phone: 000-346-4175