



SELECTIVE CALL ROOM UNIT, LIGHT ALMOND

IC7001-LA | [radiant](#)

FEATURES & BENEFITS

The radiant® Selective Call Intercom Room Unit delivers convenient room-to-room communication in up to 32 locations, all from an in-wall control point. The IC7001's high-resolution LCD screen and customizable room naming offer intuitive navigation, making the system a breeze to use.

radiant® Screwless Wall Plate not included.

- Room-to-room communication for up to 32 locations
- Support for calling, hands-free replying, monitoring, do not disturb and mute
- High resolution color LCD display with intuitive navigation
- Custom room names for a truly personalized user experience
- Room grouping and broadcast for easy calling of multiple locations at once
- Hands-free Call Reply
- Part of the radiant Collection
- Supports three simultaneous conversations

SPECIFICATIONS

GENERAL INFO

Color: Light Almond

CONSTRUCTION INFORMATION

Material 1: ABS Plastic/Steel

DIMENSIONS

Overall Dimensions (US): 4 7/8" x 4 7/8"

Weight: 1 lb

CORD INFORMATION

Pinning:

1. 24 VDC

OUT
2. GND
3. Audio (+)
4. COMM A
5. COMM B
6. Audio (-)
7. NOT
USED
8. NOT
USED

TECHNICAL INFORMATION

Cat5 Cable Rating: CAT5 UTP, 4 pair solid conductor (24 AWG)
Firmware Update: 6 Pin Header Connector
Humidity: Up to 90% RH (non-condensing)
LCD Color Depth (US): 16 Bit Color
LCD Size (US): 1.47 Diagonal
Material: ABS Plastic/Steel
Operating Temperature (Celsius): 0 to 55°C
Power Requirements: +24 Vdc, +/-1.25 Vdc, 0.25 A max
QLink Selective Call Ports: RJ-45
Storage Temperature: -55 to 75°C