



WHISPER™ WI-FI READY REMOTE DIMMER SWITCH, MAGNESIUM

ADWRRRM1 | [adorne](#)

FEATURES & BENEFITS

USAGE

- Perfect anywhere you'd like to combine Wi-Fi-Ready lighting control with whisper-soft motion to dim and brighten lights.
- The Whisper Wi-Fi Ready Remote Dimmer is a programmable light switch and dimmer combination that pairs with the adorne Hub and the Whisper Wi-Fi Ready Master Dimmer to create smart lighting solutions for your home.
- Turn lights on and off or dim with whisper-soft motion – or create custom lighting settings to control lights from your smartphone or tablet via the Legrand Lighting Control app.
- Compatible with the Google Assistant and Amazon Alexa
- This item is also available in white and graphite.

GETTING STARTED

- Time to install: 25 minutes or less.
- The Whisper Wi-Fi Ready Remote Dimmer lets you control a light from a new location without running new wires. Simply install and pair with a Whisper Wi-Fi Ready Master Dimmer via the easy-to-follow instructions.
- This item is meant to be paired with the Whisper Wi-Fi Ready Master Dimmer, which installs directly to the light. Together they allow for customizable control of a single lighting source from two locations or from your smartphone.
- The Legrand Lighting Control app is available for free on iTunes and Google Play.
- This item requires the [adorne Hub](#). [Shop now](#) to learn how Wi-Fi lighting solutions can transform your home.
- This item requires an adorne Wall Plate. [Shop now](#) to choose from dozens of finishes including a variety of luxurious metals, or order in your own custom finish.
- Looking to integrate other party advanced automation systems? Visit our [partners page](#).

SPECIFICATIONS

GENERAL INFO

Color: Magnesium
Product Series: adorne Whisper
Style: Whisper

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

FCC Standard: Yes

TECHNICAL INFORMATION

AC Voltage Output: 120VAC

Frequency: 900 MHz (RF)

Humidity: 0-80% relative humidity, noncondensing

Mounting: USA Electrical Wiring Box / adorne Mounting Plate

Operating Temperature (Celsius): 0°C to 50°C

Product Fits Into: Wall

Storage Temperature: 32°F to 122°F