



FEATURES & SPECIFICATIONS

INTENDED USE

To be powered by 6 or 12 volt battery equipment as part of an emergency lighting system providing light for the path of egress.

CONSTRUCTION

Single or twin heads available.

Fully adjustable lamp heads meet all aiming requirements.

Lamp head and mounting plate constructed of lightweight thermoplastic.

Removable bezel and slip-on lamp terminals simplify maintenance and lamp replacement.

Strong, compact and corrosion-resistant with a UL94V-0 flame rating.

OPTICS

Glass sealed-beam PAR36 lamp(s).

INSTALLATION

Universal mounting plate for use with single or twin-head applications.

Mounts to single-gang switch box.

LISTINGS

Listed in accordance with UL 1598 and CSA C22.2 No. 250.

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Catalog Number
Notes
Type



Unit Accessories

ELA

Remote Fixture

Specifications

	Mounting Base	Single	Twin
Length:	3-1/8" (79mm)	-3/4" (121mm)	13" (330mm)
Depth:		4-9/16" (116mm)	3-11/16" (93mm)
Height:	5" (127mm)	7-3/4" (197mm)	6-5/8" (168mm)
Shipping Weight:		1-3/4lbs(0.77 kg)	2lbs(0.91 kg)

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

For shortest lead times, configure product using **standard options (show in bold)**.

Example: ELA N0806

ELA				
Series	Housing color	Number of heads	Fixture	Lamp type
ELA	(blank) Desert tan W Ivory white B Black ITN Instrument tan	(blank) Single T Twin	(blank) Standard PAR36 sealed-beam	<u>PAR36 sealed-beam</u> N0806 8W/6V incandescent H0606 6W/6V halogen N1206 12W/6V incandescent H0806 8W/6V halogen N1212 12W/12V incandescent H1206 12W/6V halogen N1812 18W/12V incandescent H0812 8W/12V halogen N2512 25W/12V incandescent H1212 12W/12V halogen