





## Traditional Flush Furniture Feed FRPT 3 Inch Core Hole Units, for Use In Concrete Floors

### Large Capacity, Single-Service Flush Furniture Feed FRPT, Two-Piece Units

Description	Catalog Number	Description	Color/Material	Catalog Number
Large Capacity, Single-Service Through Floor Fitting with (1) 2 in. EMT stem. Will accommodate up to 36 Category 5e cables.	<b>PT2FIT</b>	Large Capacity Cover/Flange	Brass Finish Black Gray	<b>FF2BRS</b> <b>FF2BK</b> <b>FF2GY</b>
<p>Specifications:</p> <ul style="list-style-type: none"> <li>• 1- to 2-hour fire rating</li> <li>• Single-Service, Power or Data</li> <li>• For 2¼ to 7 in. floor thickness</li> <li>• UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area</li> <li>• Approved for use in the City of Chicago</li> </ul>		<p>Specifications:</p> <ul style="list-style-type: none"> <li>• Cover/flange with 1¼ in. and 2 in. trade size combination knockout</li> <li>• Painted aluminum cover and flange</li> <li>• Approved for use in the City of Chicago</li> </ul>		



Note: \*Includes pre-wired 20A isolated ground duplex Style Line® receptacle. See page Q-34 for technical information.

### Flush Furniture Feed FRPT, One-Piece Units



Description	Color	Catalog Number	Description	Color	Catalog Number
3-Service Furniture Feed Poke-Through	Black Gray Ivory	<b>PT73FFSDBK</b> <b>PT73FFSDGY</b> <b>PT73FFSDI</b>	Single-Service Furniture Feed Poke-Through	Black Gray Ivory	<b>PT7FFSDGY</b> <b>PT7FFSDI</b>
<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• PT73SD floor fitting</li> <li>• Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power</li> <li>• Painted aluminum flange</li> </ul>			<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• PT71SD floor fitting</li> <li>• Aluminum cover with (1) KO to accept a ¾ in. connector</li> <li>• Painted aluminum flange</li> </ul>		

Note: See page Q-34 for technical information.

### Flush Furniture Feed FRPT, Two-Piece Units

Description	Catalog Number	Description	Catalog Number
3-Service Furniture Feed Through-Floor Fitting with (1) ¾ in. EMT stem for power and (2) ½ in. low voltage conduit holes.	<b>PT73SD</b>	Single-Service Furniture Feed Through-Floor Fitting with (1) ¾ in. EMT stem for power or low voltage applications.	<b>PT71SD</b>
<p>Specifications:</p> <ul style="list-style-type: none"> <li>• 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)</li> </ul>		<p>Specifications:</p> <ul style="list-style-type: none"> <li>• For 2¼ to 7 in. floor thickness</li> <li>• UL installation spacing – minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area</li> </ul>	

### Service Fittings

Description	Color	Catalog Number	Description	Color	Catalog Number
3-Service Furniture Feed Service Fitting	Black Gray Ivory	<b>FRF3BK</b> <b>FRF3GY</b> <b>FRF3I</b>	Single-Service Furniture Feed Service Fitting	Brass Finish Black Gray	<b>FRF1BRS</b> <b>FRF1BK</b> <b>FRF1GY</b>
<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power</li> <li>• Painted aluminum flange</li> </ul>		<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• Aluminum cover with (1) KO to accept a ¾ in. connector</li> <li>• Painted aluminum flange</li> </ul>			

Note: See page Q-26 for 3 Inch FRPT accessories. See page Q-34 for technical information.