

Green Hornet® XF



Product Specifications

Application

Medium-duty, light-weight construction; retains flexibility in cold weather. Smooth-bore tube minimizes material buildup and resists a variety of chemicals found in agricultural and sanitary industries. Slightly corrugated outer helix promotes abrasion resistance, low coefficient of friction and ease of coupling. Common uses can be found in waste management, construction, agricultural, marine and manufacturing industries.

Construction Tube

Black thermoplastic rubber, RMA Class B (medium oil resistance)

Reinforcement

Rigid, lime-green polyethylene helix; available in a variety of custom colors

Temperature Range

-40°F to 180°F (-40°C to 82°C)

Packaging

100' lengths, coiled and polywrapped

Branding (Spiral)

Not branded

Couplings

Contact fitting manufacturer for proper fitting recommendation and coupling procedure

Order Codes

586-551

Green Hornet® XF

SAP #	ID		Nom. OD		Max. WP		Bend Radius		Weight	
	in.	mm	in.	mm	psi	MPa	in.	mm	lb./ft.	kg/m
20450178	1¼	31.8	1.53	39.0	50	0.35	2.5	63.5	0.27	0.40
20450177	1½	38.1	1.78	45.3	50	0.35	3	76.2	0.32	0.48
20450179	2	50.8	2.40	61.0	50	0.35	4	101.6	0.56	0.83
20450350	2½	63.5	2.99	74.9	50	0.35	5	127.0	0.75	1.12
20450351	3	76.2	3.47	88.1	45	0.31	5	127.0	0.92	1.37
20450352	4	101.6	4.67	118.4	40	0.28	9	228.6	1.60	2.39
20450353	6	152.4	6.75	171.4	25	0.17	20	508.0	2.88	4.30

Air & Multipurpose
General Purpose
Heavy Duty
Push-on

Chemical Transfer

Cleaning Equipment

Food
Transfer
Washdown

Marine

Material Handling
Abrasives
Bulk Transfer
Cement & Concrete

Mining

Petroleum
Aircraft Fueling
Dispensing
Dock
Transfer

Spray

Steam

Vacuum

LPG Delivery

Water
Discharge
Suction & Discharge
Washdown

Welding

Coupling Systems

Equipment

Appendix