

ASCO™ 210 2-Way Solenoid Valves

The ASCO Series 210, also known as 8210, is a line of economical, high-flow general service solenoid valves for liquid, corrosive, and air/inert gas service. With a wide range of pressure ratings, sizes, and resilient materials, the ultra-reliable 2-way solenoid valves provide long service life and low internal leakage. Industrial applications include car wash equipment, air compressors, pumps, laundry equipment, and industrial water control.



Technical data

| | |
|-------------------------|--|
| Valve Actuation | Solenoid |
| Function | 2 way - 2/2 Normally Closed |
| Body Material | Brass |
| Flow (Cv) | 13 Cv |
| Pipe/Port Type and Size | 1 NPT |
| Media | Air Inert Gas Water Light Oil |
| Min Ambient Temperature | 32 °F |
| Max Ambient Temperature | 104 °F |
| Min Fluid Temperature | 32 °F |
| Max Fluid Temperature | 180 °F |
| Product Weight | 4.61 lbs |
| Voltage and Frequency | 110, 120 Volts AC / 50/60 Hz |
| Watt Rating | 15.4 W |
| Orifice Size | 1 in |
| Coil Class | FT |
| Carton Note | 1 X 1 2NC BRASS 15.4/F AC |
| Kit Number | 302283 |

Part No.

8210B054AC120/60,110/50D