

## ASCO™ 210 2-Way Solenoid Valves

The ASCO Series 210, also known as 8210, is a line of economical, high-flow general service solenoid valves for liquid, corrosive, and air/inert gas service. With a wide range of pressure ratings, sizes, and resilient materials, the ultra-reliable 2-way solenoid valves provide long service life and low internal leakage. Industrial applications include car wash equipment, air compressors, pumps, laundry equipment, and industrial water control.



### Technical data

Valve Actuation	Solenoid
Function	2 way - 2/2 Normally Closed
Body Material	Brass
Seating Elastomer	NBR
Flow (Cv)	5 Cv
Pipe/Port Type and Size	3/4 NPT
Media	Air Inert Gas Water Light Oil
Min Operating Pressure (Air)	5 psi
Max Operating Pressure (Air)	100 psi
Min Operating Pressure (Water)	5 psi
Max Operating Pressure (Water)	90 psi
Min Operating Pressure (Light Oil)	5 psi
Max Operating Pressure (Light Oil)	75 psi
Min Ambient Temperature	32 °F
Max Ambient Temperature	104 °F
Min Fluid Temperature	32 °F
Max Fluid Temperature	150 °F

Product Weight	2.09 lbs
Voltage and Frequency	12 Volts DC
Watt Rating	11.6 W
Orifice Size	3/4 in
Coil Class	FT
Lead Length	18 inch
Mounting Direction	Any
Carton Note	3/4 X 3/4 2NC BRASS 11.6/F DC
Kit Number	302376
Order Code	20120
Part No.	8210G009DC12/DCD