

ASCO™ 210 2-Way Solenoid Valves

The ASCO Series 210, also known as 8210, is a line of economical, high-flow general service solenoid valves for liquid, corrosive, and air/inert gas service. With a wide range of pressure ratings, sizes, and resilient materials, the ultra-reliable 2-way solenoid valves provide long service life and low internal leakage. Industrial applications include car wash equipment, air compressors, pumps, laundry equipment, and industrial water control.



Technical data

Valve Actuation	Solenoid
Function	2 way - 2/2 Normally Open
Body Material	Brass
Seating Elastomer	NBR
Flow (Cv)	5.5 Cv
Pipe/Port Type and Size	3/4 NPT
Media	Air Inert Gas Water Light Oil
Min Ambient Temperature	32 °F
Max Ambient Temperature	104 °F
Min Fluid Temperature	32 °F
Max Fluid Temperature	150 °F
Product Weight	3.24 lbs
Voltage and Frequency	24 Volts DC
Watt Rating	11.6 W
Orifice Size	3/4 in
Coil Class	FT
Lead Length	18 inch

Mounting Direction	Any
Carton Note	3/4 X 3/4 2NO BRASS 11.6/F DC
Kit Number	302450
Order Code	20175
Part No.	8210G035DC24/DCD