

## ASCO™ 210 2-Way Solenoid Valves

The ASCO Series 210, also known as 8210, is a line of economical, high-flow general service solenoid valves for liquid, corrosive, and air/inert gas service. With a wide range of pressure ratings, sizes, and resilient materials, the ultra-reliable 2-way solenoid valves provide long service life and low internal leakage. Industrial applications include car wash equipment, air compressors, pumps, laundry equipment, and industrial water control.



### Technical data

Valve Actuation	Solenoid
Function	2 way - 2/2 Normally Closed
Body Material	Brass
Seating Elastomer	NBR
Flow (Cv)	2.8 Cv
Pipe/Port Type and Size	3/8 NPT
Media	Fuel Gas
Min Ambient Temperature	32 °F
Max Ambient Temperature	125 °F
Min Fluid Temperature	32 °F
Max Fluid Temperature	125 °F
Product Weight	2.29 lbs
Voltage and Frequency	110 AC, 120 AC / 50/60 Hz
Watt Rating	10.1 W
Holding Current (VA)	25
Orifice Size	5/8 in
Coil Class	FT
Lead Length	18 inch
Mounting Direction	Any
Carton Note	3/8 X 5/8 2NC BRASS 10.1/F AC

Kit Number	304076
Order Code	20198
Part No.	8210G074AC120/60,110/50D