

**ASCO™ 210 2-Way Solenoid Valves**

The ASCO Series 210, also known as 8210, is a line of economical, high-flow general service solenoid valves for liquid, corrosive, and air/inert gas service. With a wide range of pressure ratings, sizes, and resilient materials, the ultra-reliable 2-way solenoid valves provide long service life and low internal leakage. Industrial applications include car wash equipment, air compressors, pumps, laundry equipment, and industrial water control.



**Technical data**

Valve Actuation	Solenoid
Function	2 way - 2/2 Normally Closed
Body Material	Stainless Steel
Seating Elastomer	NBR
Flow (Cv)	1.5 Cv
Pipe/Port Type and Size	3/8 NPT
Media	Air Inert Gas Water
Min Operating Pressure (Air)	5 psi
Max Operating Pressure (Air)	40 psi
Min Operating Pressure (Water)	1 psi
Max Operating Pressure (Water)	40 psi
Product Weight	0.99 lbs
Voltage and Frequency	24 Volts DC
Watt Rating	11.6 W
Orifice Size	03.Aug
Coil Class	F
Lead Length	18 inch
Mounting Direction	Any

Carton Note

3/8 X 3/8 2NC S.S. 11.6/F DC

Kit Number

302421

Part No.

EF8210G036DC24/DCD