

### **ASCO™ 210 2-Way Solenoid Valves**

The ASCO Series 210, also known as 8210, is a line of economical, high-flow general service solenoid valves for liquid, corrosive, and air/inert gas service. With a wide range of pressure ratings, sizes, and resilient materials, the ultra-reliable 2-way solenoid valves provide long service life and low internal leakage. Industrial applications include car wash equipment, air compressors, pumps, laundry equipment, and industrial water control.



### **Technical data**

Valve Actuation	Solenoid
Function	2 way - 2/2 Normally Closed
Body Material	Brass
Seating Elastomer	NBR
Flow (Cv)	1.5 Cv
Pipe/Port Type and Size	3/8 NPT
Media	Air Inert Gas Water
Min Operating Pressure (Air)	5 psi
Max Operating Pressure (Air)	150 psi
Min Operating Pressure (Water)	1 psi
Max Operating Pressure (Water)	125 psi
Min Ambient Temperature	32 °F
Max Ambient Temperature	125 °F
Min Fluid Temperature	32 °F
Max Fluid Temperature	180 °F
Product Weight	1.61 lbs
Voltage and Frequency	120 AC / 60 Hz
Watt Rating	6.1 W

Orifice Size	03.Aug
Coil Class	FT
Lead Length	18 inch
Mounting Direction	Any
Carton Note	3/8 X 3/8 2NC BRASS 6.1/F AC
Kit Number	302271
Order Code	20195
Part No.	EF8210G073AC120/60D