

# Switch Start Metal Halide Standard

## MH1000/U 6PK

High performance, Long life and Superior light quality;A compact, energy efficient metal halide lamp that provides crisp, sparkling light wih long life and high efficiency.

### Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: [www.lamprecycle.org](http://www.lamprecycle.org) or 1-800-555-0050

### Product data

General information	
Base	E39 [ Single Contact Mogul Screw]
Operating Position	Universal [ Universal]
Main Application	General Lighting (G)
Life to 50% Failures (Nom)	12000 h
ANSI Code HID	M47/E

Light technical	
Color Code	640 [ CCT of 4000K]
Luminous Flux (Rated) (Nom)	110000 lm
Color Designation	White (WH)
Lumen Maintenance - 40% Life	65 %

Design Mean Lumens	71500 lm
Chromaticity Coordinate X (Nom)	0.385
Chromaticity Coordinate Y (Nom)	0.390
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	110 lm/W
Color Rendering Index (Nom)	65

Operating and electrical	
Lamp Current (Nom)	4.1 A
Ignition Supply Voltage (Min)	440 V
Re-Ignition Time (Min) (Max)	15 min
Ignition Time (Max)	120 s

## Switch Start Metal Halide Standard

Voltage (Max)	288 V
Voltage (Min)	238 V
Voltage (Nom)	263 V

### Mechanical and housing

Bulb Finish	Clear
Cap-Base Information	Brass [ Brass Cap]
Bulb Material	Hard Glass
Bulb Shape	BT56 [ BT56]

### Approval and application

Energy Saving Product	Not Applicable
Picogram Per Lumen Hour	176 pg/lm.h
Mercury (Hg) Content (Max)	151.0 mg

### UV

Pet (Niosh) (Nom)	59.9 h/500lx
Damage Factor D/fc (Nom)	0.7

### Luminaire design requirements

Bulb Temperature (Max)	806 °F
Cap-Base Temperature (Max)	482 °F
Cap-Base Temperature (Max)-DUP	482 °F


### Product data

Order product name	MH1000/U 6PK
EAN/UPC - Product	046677415228
Order code	415224
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	928601179901
Net Weight (Piece)	0.002 lb



Do not place in trash -  
dispose according to local,  
state, or federal laws

## Dimensional drawing



MH1000/U 6PK

Product	D	C (max)
MH1000/U 6PK	7 in	15.375 in

